

URINAL INSTALLATION INSTRUCTIONS

Mr Plumber,

All care has been taken during manufacturing to ensure the quality of this product. Please check the following points before proceeding with installation.

Check urinal for any damage that may have occurred during transportation.

Check that the fittings have been supplied i.e. drop pipes and outlet cover.

INSTALLATION

If concealed flush pipe is being used, silver solder flush pipe to elbow and check for leaks.

Set up urinal in position and connect waste to comply with water authority regulations. Check levels of tiling flanges at rear, ends and front vertical edges.

When urinal is fixed into place test for adequate drainage to waste outlet by pouring 5-10 litres of water into the trough of urinal stall.

No water should remain other than droplets due to surface tension.

Urinal must be tested for flushing performance.

Before slurry is poured around base and before rendering and tiling is commenced the urinal must be inspected for damage, if no damage is found, proceed with installation.

STORAGE AND HANDLING

Stainless steel has sharp edges. Ensure hand protection is worn when handling.

This product has a protective coating and we recommend removal after building is complete.

WARNING: DO NOT STORE THIS PRODUCT IN DIRECT SUNLIGHT AS THE COATING WILL BECOME EXTREMELY DIFFICULT TO REMOVE AND MAY DAMAGE THE PRODUCT.