

PLASTER TRAP INSTALLATION & USERS GUIDE

Congratulations on choosing a quality product from Southern Cross Laser & Sheet Metal. This plaster trap has been designed and approved by water board authorities to minimise the fouling and blocking of the drainage system in buildings. When correctly installed and maintained this unit will give many years of service and help to protect our environment.

THE PLUMBER


1. Locate the plaster trap in a position that provides a recommended minimum of 450mm clearance from lid to underside of bench top for removal of inner tank.
2. Connect 50mm trap to sink bowl and ensure water level of "S" trap is a minimum 200mm above water level of plaster trap.
3. Test all connections for leaks.

THE USER

1. Do not dispose of acids, chemicals or any other substance unsuitable for normal sink waste through this trap.
2. Do not dispose of large quantities of plaster through this trap.
3. Do not dispose of food scraps through this trap.
4. When washing down implements used with plaster ensure enough water is used to clear the "S" trap.
5. Maintenance will depend on usage, a trap used daily with high volumes of plaster will require more frequent cleaning.

MAINTENANCE INSTRUCTIONS

1. Remove lid from plaster trap.
2. Push inner tank away from inlet.
3. Remove inner tank from trap.
4. Remove screens from inner tank & clean.
5. Should the trap itself need cleaning, proceed as follows.
6. Drain the tank before disconnecting.
7. Remove the tank and clean as required.



SOUTHERN CROSS
LASER & SHEET METAL

23-27 Clapham Road
Regents Park NSW 2143

Ph: 02 9644 2811
Email office@scclaser.org